		Rev.	Desc	ription	Date
		Α			05-2019
	DB9/F			DB25 / M 13 0 0 1 1 1	-3
	Pin Assignment DB9 DB25 Female Male 1 4				
	$\begin{array}{c} 2 \\ 3 \\ \end{array} \\ \begin{array}{c} 5 \\ 2 \\ 3 \\ \end{array} \\ \begin{array}{c} 5 \\ 2 \\ 3 \\ \end{array} \\ \begin{array}{c} 7 \\ 3 \\ \end{array} \\ \end{array} \\ \begin{array}{c} 7 \\ 3 \\ \end{array} \\ \begin{array}{c} 7 \\ 3 \\ \end{array} \\ \end{array} \\ \begin{array}{c} 7 \\ 3 \\ \end{array} \\ \end{array} \\ \begin{array}{c} 7 \\ 3 \\ \end{array} \\ \end{array} \\ \begin{array}{c} 7 \\ 7 \\ 3 \\ \end{array} \\ \end{array} \\ \begin{array}{c} 7 \\ 7 \\ 7 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\$			PART NO.	CABLE LENGTH
	$\begin{bmatrix} 2 \\ 3 \\ 4 \\ 5 \end{bmatrix} = \begin{bmatrix} 2 \\ 3 \\ 6 \\ 7 \end{bmatrix} = \begin{bmatrix} RoHS \\ RoHS \end{bmatrix}$			10D1-21306	6 ft
	$\begin{array}{c} 6 \\ \hline 7 \\ \hline \end{array} \\ \hline 8 \\ \end{array}$			10D1-21310	10 ft
	$\begin{array}{c} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$			10D1-21315	15 ft
	G G			10D1-21325	25 ft
5	Molded Thumbscrew, #4-40, Beige		10D1	-213xx	
4		Null Modem Cable, DB9 Female to DB25 Male, 8 Conductor			
3	DB25 Male, w/Gold Plating Contacts, Blue Insulator				
2	DB9 Female, w/Gold Plating Contacts, Blue Insulator Drawn by:	JL	_		
1	8C 28AWG+ Drain Wire, Single Shielded with AL-Foil , Approved by: Beige Outer PVC Jacket Approved by:	MAC			
No.	Specifications ID:	1			olesale š