



Rev.	Description	Date
A		03-2024

RoHS



Pin Assignment		
DB9 Male		DB9 Female
1	Brown	1
2	Red	2
3	Orange	3
4	Yellow	4
5	Green	5
6	Blue	6
7	Purple	6
8	Gray	7
9	Black	8
G	Drain	9
		G

- NOTES:**
- Product Must be 100% Tested 4 Times, No Short, No Open Circuit and No Dislocation
 - Electronics Testing
Insulation Resistance: 5Mohm
Conductor Resistance: 5ohm
Voltage Rating: 300V
 - Temperature Range: -10 ~ +70 Degree



PART NO.	LENGTH CABLE
10D1-03201	1 ft
10D1-03203	3 ft
10D1-03206	6 ft
10D1-03210	10 ft
10D1-03215	15 ft
10D1-03250	50 ft
10D1-032HD	100 ft

6	Molded Thumbscrew,#4-40, Beige	Item Number:	10D1-032xx	
5	Outer Molded PVC Beige		Title:	Serial Extension Cable, DB9 Male to DB9 Female, RS-232, UL rated, 9 Conductor, 1:1
4	Inner Molded LDPE Transparent	Drawn by:		JL
3	DB9 Female, w/ Gold Plating on Contacts, Blue Insulator		Approved by:	MAC
2	DB9 Male, w/ Gold Plating on Contacts, Blue Insulator	ID:		115
1	UL2464 Cable, 9C 28AWG(7/0.12BC)+ Drain 26AWG(7/0.16BC), Single Shielded with AL-Foil, Beige Outer PVC Jacket			
No.	Specifications			