## Product Specification


REV.	DESCRIPTION	DATE
Α		03-2008
В		03-2015

## Construction & Material

Part Number	Color
10F5-0471TH	Red
10F5-0491TH	White

Item		Specification	
Product		FPLR, Fire Alarm / Security	
Conductor	Construction	Solid 4x18AWG	
Conductor	Material	Bare Copper	
	Material	PVC	
Insulation	Min.thickness		
msulation	Avg. thickness	0.254 mm	
	Diameter	1.524 mm	
Nom. Lay Length		127 mm	
	Color		
	Material	PVC	
Jacket	Min.thickness	Black, Red. Yellow and Blue	
Judeket	Avg. thickness	0.381 mm	
	Diameter	4.445 mm	
	Color	Red and White	
Approximate Cable Weight		29 lbs./Kft	

## Cross Section:



Temperature Rating		−20 °C to 60 °C		<b>\rightarrow</b>	$\Box$
Operating Voltage		300 V/RMS max	۲.	APPROVED	
Capacitance Between Conductors@1KHz		35 pF/ft.nom.		CHECKED	
Nom. DC Resistance per	Conductor@20°C	6.43 Ohms/Kft.r	nom.	DRAWER	JL
Electrical Properties:					

	PART NUMBER:	TITLE:
ID(NO.)	10F5-04xxTF	4/18 Solid FPLR
204		Pullbox, 500 ft

