


Rev.	Description	Date
A		05-2021

RoHS

Cross Section




Product Specifications

Construction & Material :

Item		Specifications
Product		CMR Security/Alarm Wire
Conductor	Construction	Stranded, 4 x22AWG(7/0.25mm)
	Material	Bare Copper
Insulation	Material	PVC
	Avg.thickness	0.15mm
	Diameter	1.0± 0.05 mm
	Color	Black, Red, White and Green
Jacket	Material	PVC
	Avg.thickness	0.38 mm
	Diameter	OD Average 2.464 / Final Diameter 3.327mm
	Color	Gray
Marking	STRUCTURED CABLE PRODUCTS --- P/N 22/4 --- (UL) CL3R Exxxxxx-SCP (UL) C(UL) CMR UNSH 4/C 22 AWG --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS	

Characteristics	
Mutual Capacitance	38 pF/ft
DC Resistance 25°C	15.8 Ohms / 1000 ft
Impedance	80 Ohms
Velocity of Prop	63 %
Inductance	1.4 mH/km
Temp/Voltage	60°C / 300V
Operating Temperature	-20°C to 60°C

PART NO.	Length	Weigth
10K4-04212SF	500FT	7 lbs / 3 kgs
10K4-04212SH	1000FT	15 lbs / 7 kgs

Item Number:	10K4-04212Sx	
Title:	Security/Alarm Wire, Gray, 22/4 (22AWG 4 Conductor), Stranded, CMR / Inwall rated, Pullbox	
Drawn by:	JL	
Approved by:	MAC	
ID:	123	

No.	Specifications
-----	----------------