


Rev.	Description	Date
A		04-2022




BLACK INK MARKING: USB 3.0 CABLE 28AWG  $\Omega$  AWM E139315-F5 STYLE 2725 80°C 30V VW-1

A  
4:1

B  
4:1

**Pin Assignment**


Standard_A Plug		Wire		Micro_B Plug	
Pin	Signal Name	Wire	Signal Name	Pin	Signal Name
1	VBUS	1	PWR	1	VBUS
2	D-	2	UTP_D-	2	D-
3	D+	3	UTP_D+	3	D+
4	GND	4	GND_PWRrt	5	GND
5	SSRX-	5	SDP1-	6	SSTX-
6	SSRX+	6	SDP1+	7	SSTX+
7	GND_Drain	7、10	SDP1_Drain SDP2_Drain	8	GND_Drain
8	SSTX-	8	SDP2-	9	SSRX-
9	SSTX+	9	SDP2+	10	SSRX+
--	-	-	-	4	ID
Shell	Shield	Braid	Shield	Shell	Shield



SECTION A-A

RoHS

Rating Temperature: 10°C ~+80°C  
 Rating Voltage: 30V  
 Insulation Resistance: DC 250V 10MΩ Min.  
 Withstand Voltage: AC 250V 5mA for one Minute.  
 Conductor Resistance: 2Ω Max.

Item Number:	10U3-03103	
Title:	3ft Blue Micro USB 3.0 Cable, Type A to Micro Type B	
Drawn by:	JL	
Approved by:	MAC	
ID:	108	

No.	Specifications
4	Outer Molding PVC Blue
3	USB 3.0 Micro B Male Plug, Terminal: Phos/Brass, Gold Plated G/F
2	USB 3.0 A Male Plug, Terminal: Phos/Brass, Gold Plated G/F
1	USB 3.0 Cable: 3P*28AWG+2C*28AWG