



PIN OUT :

BNC
 1 CORE BNC
 2 BRAID 2

P/N	LENGTH	1PCS/PE BAG	10PCS/PE BAG
10X1-01101	305 ± 10	06*3"*8"	06*6"*11"
10X1-01103	915 ± 20	06*5"*7"	06*8"*12"
10X1-01104	1220 ± 30	06*5"*7"	06*8"*12"
10X1-01106	1830 ± 50	06*6"*8"	06*10"*13"
10X1-01110	3050 ± 60	06*6"*8"	06*10"*13"
10X1-01115	4575 ± 60	06*6"*8"	06*10"*13"
10X1-01125	7625 ± 80	06*6"*11"	
10X1-01150	15250 ± 100	06*9"*13"	
10X1-01175	22875 ± 100	06*10"*13"	
10X1-011HD	30500 ± 100	06*11"*16"	

MATERIAL LIST :

NO.	P/NAME	DESCRIPTION	Q'TY
1	CABLE	RG58 20AWG(STRAINED CCS ID: 2.95 TEXTURE OF MATERIAL: PE) +AL+1+B(16*5/0.12 CCA) OD: 5.0 ± 0.15 BLACK (B792)	1
2	CONN	BNC MALE 50ohm	2
3	PVC	45P BLACK (B792) PVC	11g
4	PACKING	All connector and cable, everything below 15ft should be packed with single PE bag (Marking Item and ROHS). Every 10 piece should be packed with a larger PE bag. No marking necessary for the larger PE bag.	1
5	CTN	PCS/CTN (39*39*27CM)	1

MOLD TOOL NO.		CABLEWHOLESALE.COM		DRAWN BY liang	
FILE NAME 0W0710001		SCALE	UNIT	REV	CONFIRMED BY
DATE 17/08/28	CUSTOMER P/N	MM	A	CHECKED BY	APPROVED BY

ROHS