




Notes

CableWholesale Duplex Cable is composed of a tight buffer, aramid yarn, and a PVC outer jacket. All component materials meet the EU RoHS and REACH Directive standards.

CWS Duplex Cable is available in 12 TIA standard colors or special order colors. UL Listed OFNP cables are available, and unlisted, unrated cables can be supplied to accommodate special needs. Standard surface print denotes construction, NEC rating, and fiber type, and includes footage markers. Custom print can also be accommodated.



Application

Plenum

Flame Rating

NFPA262

REV.	DESCRIPTION	DATE
A		09-2014
B		06-2015

**Product Specifications**

Construction & Material :

Item	Specifications
Product	Multimode, Duplex, 62.5/125
Fiber Count	2
Outer Jacket Material	Flame Retardant PVC
Outer Jacket Color	Orange
Strength Member	Aramid Yarn
Tight Buffer Material	Flame Retardant PVC
Tight Buffer Color	Available in 12 TIA/ EIA color standard

Physical Characteristics	Value
Nominal Outer Diameter (mm)	2.95 x 5.95
Weight (lbs/ km)	40
Minimum Bend Radius (mm) (Bend Insensitive MM)	7.5

Optical Characteristics

Items	62.5/125
Core Size	62.5 um
Wavelength	(850/ 1300) nm
Max. Attenuation	(3.5/ 1.5) dB/ Km
Bandwidth (EMB) (High Performance)	220 MHz @850nm

DRAWER	JL
CHECKED	
APPROVED	

Storage Temp		-40 °C / +70 °C
Operating Temp		0 °C / +70 °C
ID(NO.)	PART NUMBER	TITLE
120	11F1-111NH	Bulk Plenum Zipcord Fiber Optic Cable, Multimode, Duplex, 62.5/125, Orange, Spool, 1000 foot

