

## Overview

Cablewholesale Armored Fiber Optic Cable is used in building wiring applications. It can be installed in walls, between floors, in plenum air handling ducts and under data center floors indoor or indoor/outdoor application. The armored cable consists of 0.9mm tight buffered fiber surrounded by yarn acting as a strength member. The core is protected by a spirally-wrapped steel tube that offers easy installation and high crush resistance.


Its structure contains stainless steel armor inside the jacket, this will help make the armored fiber patch cord resistant of high tension and pressure and it is not easy to break when bent or dragged. The stainless steel tube prevents optic fiber from damage that improves stability of the system.

## Features

- It is flexible, anti-rodent, pressure resistance.
- The structure is Anti-rodent ringed steel protection & External reinforced aramid yarn protection
- High tensile strength, pressure resistant, rodent protected.
- Good mechanical and environmental characteristics
- Flame retardant characteristics
- Soft, flexible, easy to splice, and with big capacity data transmission
- Anti rodent and UV stable

## Application

- Widely used in FTTH access network
- Telecommunication Networks
- CCTV Networks
- Data communications Networks
- Local Area Networks



**Cross Section**

Rev.	Description	Date
A		06-2022

**RoHS**

## Optical Fiber Characteristics

Fiber Type	CORNING InfiniCor 300 62.5/125 OM1
Core Size	62.5um
Wavelength	850nm/1300nm
Max. Attenuation	(3.5/1.5)dB/km
Bandwidth(EMB) (High Performance)	850nm: 200MHz
Link Length(10Gb/s)	/
Cladding diameter(um)	125±2.0
Core-Clad Concentricity	≤1.5 um
Cladding non-circularity(%)	≤1.0
Coating-Cladding concentricity(um)	≤12.0
Coating diameter(um)	242±5
Core diameter(um)	62.5±2.5um
Effective Group Index of Refraction(Neff)	850nm:1.496 1300nm:1.491
Fatigue Resistance Parameter(Nd)	20
Temperature Dependence	-60~85 °C
Temperature-humidity cycling	-10 to +85°C, 98% R.H.

## Cable Parameters

Product	Multimode 62.5/125 OM1
Fiber Count	6 cores
Fiber Type	CORNING Glass
Cable Type	900um Tight Buffered
Tight buffer material	PVC
Strength Member	Aramid Yarn
Armor	Spiral steel armor
Cable Color	Black
Outer Jacket	Plenum rated

## Technical Parameter

Fiber Count	6	
Outer Diameter (mm)	6.0±0.3	
Nominal Weight(KG/KM)	45	
Max.Tensile Strength(N)	Short-term	1200
	Long-term	600
Min. Bending Radius (mm)	Dynamic	120
	Static	60
Max.Lateral Pressure N/100mm	3000	

Item Number:	21F3-206NF
Title:	Armored 6 Fiber Indoor/Outdoor Fiber Optic Cable, Multimode 62.5/125 OM1, Corning, Plenum, Black, Spool, 500ft
Drawn by:	JL
Approved by:	MAC
ID:	399

